

# SPACERFIX™ on demand

## Your data :


Company : \_\_\_\_\_ Contact person name : \_\_\_\_\_  
 Address : \_\_\_\_\_ Postal Code : \_\_\_\_\_ City : \_\_\_\_\_  
 \_\_\_\_\_ Country : \_\_\_\_\_  
 \_\_\_\_\_ Phone : \_\_\_\_\_ Fax : \_\_\_\_\_  
 e-mail : \_\_\_\_\_ Web Site : \_\_\_\_\_  
 Industry : \_\_\_\_\_

## 1 SPACERFIX™ MATERIAL

STEEL  STAINLESS STEEL  316L STAINLESS STEEL  HR STAINLESS STEEL  ALUMINIUM  OTHER


## 2 MORPHOLOGY

### 2.1 THREADED BODY



HEAD :


Open



Closed



Concealed



THREADS :

Ø M \_\_\_\_\_

Ø UNC \_\_\_\_\_

Ø UNF \_\_\_\_\_

standard pitch

fine pitch

other : \_\_\_\_\_

Threaded length :

standard

other : \_\_\_\_\_ mm

Threads type :

standard

reversed


completely threaded

DIMENSIONS : Ø D :  standard

L : \_\_\_\_\_ mm


other : \_\_\_\_\_ mm

### 2.2 BEARING BODY



HEAD :


Open



Closed



Concealed



DIMENSIONS : Ø D :  standard

other : \_\_\_\_\_ mm


Ø d :  standard

other : \_\_\_\_\_ mm

L :  standard

other : \_\_\_\_\_ mm

## 2.3 AXIS BODY




HEAD :

Closed




DIMENSIONS : Ø D : \_\_\_\_\_ mm  
L : \_\_\_\_\_ mm

Concealed



## 2.4 SNAP-ON BODY




HEAD :

Closed




Concealed



DIMENSIONS : Ø D :  standard  
Ø d :  standard  
L : \_\_\_\_\_ mm

other : \_\_\_\_\_ mm  
 other : \_\_\_\_\_ mm  
L1 : \_\_\_\_\_ mm

## 2.5 LOCKABLE BODY




HEAD :

Closed



Concealed




DIMENSIONS : Ø D :  standard  
Ø d1 :  standard  
Ø d2 :  standard  
L : \_\_\_\_\_ mm

other : \_\_\_\_\_ mm  
 other : \_\_\_\_\_ mm  
 other : \_\_\_\_\_ mm  
L1 : \_\_\_\_\_ mm

L2 : \_\_\_\_\_ mm

## 2.6 THREADED BODY




HEAD :

Closed



Concealed



THREADS :  Ø M\_\_\_\_  
 Ø UNC\_\_\_\_  
 Ø UNF\_\_\_\_  
L1 : \_\_\_\_\_ mm

standard pitch  
 fine pitch  
 other : \_\_\_\_\_

DIMENSIONS : Ø D : \_\_\_\_\_ mm

L : \_\_\_\_\_ mm

### 3 APPLICATION

#### CHARACTERISTICS OF THE WORKPIECE RECEIVING SPACERFIX™

Minimum thickness : \_\_\_\_\_ mm / Maximum : \_\_\_\_\_ mm


Material : \_\_\_\_\_ Hardness : \_\_\_\_\_

Final product : \_\_\_\_\_

### 4 MECHANICAL REQUIREMENTS

Standard

Special :



Push-out force : \_\_\_\_\_ daN

Tensile force : \_\_\_\_\_ daN

Direct torque force : \_\_\_\_\_ Nm

Indirect torque force : \_\_\_\_\_ Nm

Other \_\_\_\_\_

### 5 THREAD LOCK CHARACTERISTICS

Requirements :

First screwing self-locking torque : \_\_\_\_\_ Nm

First unscrewing self-locking torque : \_\_\_\_\_ Nm

Fifth unscrewing self-locking torque : \_\_\_\_\_ Nm

### 6 FINISH

Corrosion resistance required : Standard : \_\_\_\_\_

White rust : \_\_\_\_\_ h

Red rust : \_\_\_\_\_ h

Friction coefficient required : \_\_\_\_\_

Finish required : \_\_\_\_\_

### 7 VOLUMES

Batch quantity required : \_\_\_\_\_

Forecast :

Yearly quantity : \_\_\_\_\_

2<sup>nd</sup> year : \_\_\_\_\_ parts

Application lifetime : \_\_\_\_\_

3<sup>rd</sup> year : \_\_\_\_\_ parts